

Spot-check-monitor for customized configuration

seca
Precision for health

seca mVSA 535

- + Precise measurement of vital signs: blood pressure, SpO₂, pulse and temperature
- + Modular design for individual configuration
- + Easy-to-understand graphical presentation of the measurement results on the touchscreen monitor
- + Large internal memory for up to 70,000 measurements
- + Integrated replaceable rechargeable lithium-ion battery in the monitor
- + EMR-validated: transmit measured data directly to any Electronic Medical Record (EMR) system



The Spot-check-monitor to ease your workflow

The easy-to-use device measures the primary four vital signs: blood pressure, SpO₂, pulse rate, and temperature. With the wireless connectivity to all seca 360° products, height, weight and BMI are immediately and error-free available on the monitor.



Technical Data

GENERAL

Dimensions (WxHxD)	254 x 262 x 278 mm / 9.9 x 10.3 x 10.9"		
Net weight	approx. 4.6 kg / 10.1 lbs (depending on configuration)		
Box dimensions (WxHxD)	290 x 490 x 380 mm / 11.4 x 19.3 x 14.9"		
Box gross weight	approx. 6 kg / 13.2 lbs (depending on configuration)		
Box volume	0.053 m ³ / 1.87 ft ³		
Display type	7" touchscreen display		
Interfaces	Wi-Fi (IEEE 802.11 b/g/n), LAN (IEEE 802.3u), USB 2.0 (2 ports), seca 360° wireless technology (proprietary)		
Power supply	Internal power supply unit: Type IEC 60320 C13 Supply voltage 100 V ~ – 240 V ~ Supply frequency 50 Hz – 60 Hz Current consumption 0.85 A	Mobile Power supply: Type Voltage Capacity Range	Lithium-ion battery 11.25 V 2950 mAh approx. 5 h

Power consumption Standby (touchscreen display off, ON/OFF button green) <5 W; In operation (ON/OFF button white) <9 W;
Operation (battery charging, monitor, on/off button illuminated white) <35 W

Compatible printers Microsoft® Windows®-compatible printer via seca analytics 115 PC software

BLOOD PRESSURE MEASUREMENT

Measuring method	oscillometric, deflation or inflation measurement		
Measurement range	Deflation measurement: Systolic BP 25 mmHg – 280 mmHg Diastolic BP 10 mmHg – 220 mmHg	Inflation measurement: Systolic BP 77 mmHg – 200 mmHg Diastolic BP 45 mmHg – 190 mmHg	
Measurement accuracy (clinically validated according to ISO 81060)	Measurement accuracy of deflation measurement: Mean deviation systole 0.10 mmHg Standard deviation systole 3.24 mmHg Mean deviation diastole -0.20 mmHg Standard deviation diastole 2.95 mmHg	Measurement accuracy of inflation measurement: Mean deviation systole 0.36 mmHg Standard deviation systole 4.27 mmHg Mean deviation diastole -0.12 mmHg Standard deviation diastole 3.78 mmHg	
Measurement certainty	Maximum cuff pressure 300 mmHg; automatic pressure release > 330 mmHg		
Measurement time	Normal: 15 – 20 seconds / max. 90 seconds (adults)		
Measuring range (PR)	Deflation measurement: 30 min ⁻¹ – 240 min ⁻¹ / Inflation measurement: 45 min ⁻¹ – 200 min ⁻¹		
Measurement accuracy (PR) (under laboratory conditions)	max. +/- 3 min ⁻¹ / 3% (the larger value applies)		

SPO₂

Measurement method	Masimo RD SET® Spectrophotometry (red/infrared)		
Measurement range (SpO ₂)	0 – 100 %		
Measurement accuracy (SpO ₂)	SpO ₂ (no motion) 70 % – 100 % ± 2 digits SpO ₂ (in motion) 70 % – 100 % ± 3 digits		
Measurement range (PR)	PR 25 bpm to 240 bpm Perfusion index measurement range 0.02 % – 20 %		
Measurement accuracy (PR)	PR (no motion) 25 min ⁻¹ – 240 min ⁻¹ ± 3 digits PR (in motion) 25 min ⁻¹ – 240 min ⁻¹ ± 5 digits		

TEMPERATURE MEASUREMENT

Measurement methods	COVIDIEN™ FILAC™ 3000 axillary/oral, rectal (direct or predictive)		
Measurement range	direct 30 °C – 43 °C (86 °F – 109.4 °F) predictive 35.5 °C – 42 °C (95.9 °F – 107.6 °F)		
Measurement accuracy	direct ± 0.1 °C (± 0.2 °F) predictive ± 0.1 °C (± 0.2 °F)		
Measurement time	direct 60 – 120 seconds predictive (oral) 3 – 10 seconds predictive (axillary) 8 – 12 seconds predictive (rectal) 10 – 14 seconds		
Probe covers	490 0015		

ACCESSORIES

Blood pressure	Blood pressure cuffs, sizes: S: 17 – 26 cm (6.7 – 10.2"); M: 24 – 32 cm (9.4 – 12.6"); L: 32 – 42 cm (12.6 – 16.5"); XL: 38 – 46 cm (15 – 18.1") extension tube for cuffs		
SpO ₂	Masimo RD SET Series sensors and patient cables*		
Temperature	COVIDIEN™ FILAC™ 3000 probe covers 490 0015		
seca 360° wireless	Optional wireless PC software seca analytics 115, system compatible with seca 360° wireless measuring systems and scales		
Mobile use	Rolling stand seca 4750535, carrying case seca 432		